# Versatile, PC-Connectable Label Maker With Color Display









11 11 11



# **PT-D600**

With its full-color display, the PT-D600 enables users to preview the label, including the tape color installed. Simply connect it to your Windows® or Mac® computer to create professional-looking labels using P-touch Editor label design software, or use it on its own. Its super-fast print speeds and automatic tape cutter support high volume labeling tasks. Capable of printing on TZe tapes up to 24mm wide, it's ideal for a variety of label usages requiring durable labels that withstand water, heat, and fading.



#### **Key Features at a Glance:**

- Full-color display offers a true WYSIWYG experience
- Use stand-alone, or connected to a PC or Mac for added design capabilities
- High-resolution output, for crisp graphic and logo printing<sup>^</sup>
- Super-fast printing with auto cutter for high-volume jobs
- Create labels with up to 7 lines of text and graphics
- Personalize with hundreds of built-in symbols, frames, and barcodes
- Built-in templates and 99 label memory help save time with reprinting
- Uses durable, laminated labels for indoor or outdoor use
- 2-year limited warranty and free phone support for the life of the product

#### Hardware Features:

Display	Full color with backlight
Display Size	20 characters x 3 lines
Maximim Tape Width	24mm
Built-in Memory	Up to 99 labels
Keyboard	QWERTY
Tape Cutter	Automatic
Maximum Print Speed	30mm/sec. <sup>¥</sup>
Maximum Print Resolution	180 dpi (Max. 180 x 360 dpi) <sup>^</sup>
Maximum Print Height	18.0mm
Power Source	6 x AA Batteries (optional) AC Power Adapter (included)
Auto Power Off	Yes
Interface	USB
ENERGY STAR <sup>®</sup> Qualified	Yes

### Logistics Information:

UPC Code	012502639411	
Unit Dimensions	7.9" x 7.6" x 3.4"	
Unit Weight	2.1 lbs.	
Carton Dimensions	10.3" x 4.8" x 12.6"	

#### Accessories\*:

AD-E001	AC Power Adapter (included)							
CC-D600	Carry Case (optional)							

See next page for a detailed list of compatible tapes.\*

#### Carton Contents<sup>•</sup>:

#### PT-D600 Label Printer

Black on White Standard Laminated TZe Starter Tape 0.94" (24mm) x 13.1' (4m)

**AC Power Adapter** 

**USB** Cable

User's Guide

## Software Features:

Number of Fonts	14 <sup>△</sup> / TrueType <sup>±</sup>
Types of Fonts	Helsinki, Brussels, Belgium, Florida, Los Angeles, San Diego, US, Calgary, Atlanta, Adams, Brunei, Sofia, Germany, LetterGothic
Number of Font Styles	11 <sup>△</sup> / TrueType <sup>±</sup>
Number of Font Sizes	8 <sup>△</sup> / Scalable <sup>±</sup>
Maximum Print Lines	7 <sup>△</sup> / Variable <sup>±</sup>
Built-in Symbols	617 <sup>△</sup> / TrueType <sup>±</sup>
Built-in Frames	99 <sup>△</sup> / 126 <sup>±</sup>
Auto Numbering	1-99, A-Z, a-z <sup>△</sup> , 1-5,000, A-Z, a-z <sup>±</sup>
Repeat Printing	Up to 99 copies <sup><math>\Delta</math></sup> , up to 5,000 copies <sup><math>\pm</math></sup>
Vertical Printing	Yes
Mirror Printing	Yes
Auto Formats	Yes
Built-in Label Templates	Yes - Label Collection
Barcode Printing	9 kinds (CODE39, ITF 2/5, EAN13, EAN8, UPC-A, UPC-E, CODABAR, GS1-128(UCC/EAN128), CODE128)
Supports Database Printing	Yes <sup>♦</sup>
Number of Languages Supported	20
Operating Systems Compatibility•	Windows Vista, Windows 7, Windows 8/8.1 Mac OS X v.10.7.5, 10.8.x, 10.9.x, 10.10.x.

Additional purchase required

∆ When operating in stand alone mode ¥ Using AC adapter

± Using P-touch Editor 5.1 software. P-touch Editor software/drivers for Windows/Mac available as a free download at www.brother.com/inst/

- · Windows only
- P-touch Editor software/drivers for Windows/Mac available as a free download at www.brother.com/inst/ When connected to a computer

Images are for illustrative purposes only. Actual output (such as font and margins) may vary All trademarks referenced herein are the property of their respective companies All specifications subject to change without notice



There are a variety of tapes for the PT-D600. Brother TZe standard laminated tapes are great for your everyday home, home office, and general business labeling needs. These tapes feature our standard adhesive, which is designed for flat surfaces like paper, file folders, and binders, and also most even non-textured metal, plastic, and glass surfaces. They withstand water, grease, fading, and abrasion, and can be used in hot and cold environments, as well as outdoors. There are also a variety of TZe speciality tapes available for this machine, listed below.

TZe S	tandard	l Laminc	ated Tap	oes - 8m	n long
	6mm	9mm	12mm	18mm	24mm
BLACK ON WHITE	TZe211	TZe221	TZe231	TZe241	TZe251
BLACK ON CLEAR	TZe111	TZe121	TZe131	TZe141	TZe151
BLACK ON RED		TZe421		TZe441	TZe451
BLACK ON YELLOW			TZe631	TZe641	TZe651
BLACK ON GREEN				TZe741	
BLACK ON BLUE				<b>TZ</b> e541	
LACK ON FL. ORANGE*				TZeB41*	TZeB51*
WHITE ON BLACK	TZe315	TZe325	TZe335	TZe345	TZe355
WHITE ON CLEAR			TZe135	TZe145	
WHITE ON BLUE				TZe545	
RED ON WHITE			TZe232	TZe242	TZe252
BLUE ON WHITE				<b>TZ</b> e243	
GOLD ON BLACK			TZe334	TZe344	TZe354
g					
Extra Strength A	Adhesive	Laminc	ated Tap	bes - 8n	n long
	6mm	9mm	12mm	18mm	24mm
BLACK ON WHITE	TZeS211	TZeS221	TZeS231	TZeS241	TZeS251
BLACK ON CLEAR		TZeS121	TZeS131	TZeS141	TZeS151

BLACK ON MATTE SILVER			TZeS941	TZeS951
WHITE ON CLEAR		TZeS135		
BLACK ON YELLOW	TZeS621	TZeS631	TZeS641	TZeS651
BLACK ON CLEAR	1ZeS121	1ZeS131	1ZeS141	1ZeS151

	TZe Simply Stylish Tapes - 5m long							
	6mm	9mm	12mm	18mm	24mm			
WHITE ON LIME GREEN			TZeMQG35					
WHITE ON BERRY PINK			TZeMQP35					
WHITE ON SATIN GOLD			TZeMQ835					
GOLD ON SATIN SILVER			TZeMQ934					

BLACK ON WHITE

Additional purchase required.
Claims that adhesive is "acid-free" and/or "photo-safe" are based upon: 1. Satisfactory test results obtained from Photographic Activity Tests per ISO14523 and non-acidic pH tests per TAPPI 509; 2. Certifications from material

manufacturers; and 3. Atomic scans of adhesive following removal of backing paper 3m long

other narrow spaces

TZeN201

DURABLE / CRACK & PEEL NATED TAPE





nages are for illustrative purposes only. Actual output (such as font and margins) may vary. All trademarks referenced herein are the property of their respective companies All specifications subject to change without notice.